

TRACTOR		M8-191	M8-211
Engine	Engine	B6.7L Tier 4 Final / Stage V	
	Manufacturer	Cummins	
	Displacement	6.7L	
	NO. of Cylinders	6	
	Aftertreatment	DOC+SCR+DPF	
	Rated HP*	190* @ 2100	210* @ 2100
	Fuel tank Capacity Gal (L)	99 Gal (375)	
	Def Tank Capacity Gal (L)	9 Gal (35)	
Transmission	Semi-Powershift	30×15(6PX5S) 24.8MPH (40km/h) STD 31 MPH (50km/h) OPT	
	KVT	CVT 24.8MPH (40km/h) STD 31 MPH (50km/h) OPT	
PTO	Type	Electro-Hydraulically operated	
	Rear Spline	540 - 6 spline/1000 - 21 Spline (Optional 1000 - 20 Spline)	
	RPM	540/540E/1000/1000E	
	Output HP (rated)*	162* @ 2100	178* @ 2100
	Front PTO Type - Optional	Electro-Hydraulically operated	
	Front PTO RPM	1000 - 21 Spline, clockwise	
Hydraulics	Hydraulic System	Closed-Center Load Sensing (CCLS)	
	Steering/Operating Flow-gpm (L/Min)	11.1 (42)	
	Standard Implement Pump Flow-gpm (L/Min)	31.7 (120)	
	Optional Implement Pump Flow-gpm (L/Min)	42.2 (160)	
	Max flow at one EHR remote (L/Min)	31.7 (120)	
	# of (EHR) Rear Remotes	3 Standard	
	# of (EHR) Rear Remotes	5 Optional	
	Power Beyond	Optional	
	Trailer Brake (Hydraulic)	Standard	
Rear 3-Pt Hitch	3-Point Lift	CAT III/IIIN	
	Lift Cap, 24" Behind Lift Points - lbs (kg)	12478 (5660)	
	Optional: Lift Capacity - lbs (kg)	15543 (7050)	
	Ball ends	Standard	
	Hook ends	Optional	
	Drawbar - CAT III	Standard	
	Drawbar - CAT III HD	Optional	
Front 3-Pt Hitch	Category	CAT IIIN	
	Lift capacity at OECD hook - lbs (kg)*	8818 (4000)	
Front Axle	Rigid Limited Slip differential	Standard	
	Suspended Full Locking differential	Optional	
	Rigid Full-Locking differential	Optional US Models	
	Turning angle	55°	
Rear Axle	Bar Axle 105mm dia - 98" overall length	Standard	
	Bar Axle 105mm dia - 118" overall length	Optional	
Cabin	7" K-Monitor	Standard	
	12" K-Monitor Pro	Optional	
	High Visibility Roof Panel	Standard	
	Seat Fabric - Air suspension	Standard	
	Seat Fabric - Semi-active	Optional	
	Seat Leather - Semi-active heat and air conditioned	Optional	
	Radio Ready	Standard	
	Cab Suspension	Optional Semi-Active Electro - Hydraulic	
	Exterior lighting	Standard 8 Halogen / Optional 12 Halogen	
	LED lighting	Optional 12 LED	
Measurement	Wheel base - in (mm)	114 (2896)	
	Avg shipping Weight - lbs (kg)	19510 (8850)	
	Height - in (mm)	128 (3250)	

\*Factory estimated rating.

Kubota Tractor Corporation and Kubota Canada Ltd. reserve the right to change the stated specifications without notice. This material is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this material. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This material is intended for the United States, US territories, and Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.