

Specifications

Model		BX1880	BX2380	BX2680	BX23S
Engine					
Type		Liquid-cooled, 3-cylinder diesel			
Model		Kubota D722	Kubota D902	Kubota D1005	Kubota D902
Engine gross HP at 3200 rpm*1	HP (kW)	18.0 (13.4)	23.0 (17.1)	25.5 (19.0)	23.0 (17.1)
PTO horsepower at 3200 rpm	HP (kW)	13.7 (10.2)	17.7 (13.2)	19.5 (14.5)	17.7 (13.2)
Displacement	cu.in. (cc)	43.9 (719)	54.8 (898)	61.1 (1001)	54.8 (898)
Fuel tank capacity	gal. (ℓ)	6.6 (25)			
Drive train					
Transmission		HST, High-Low gear shift (2 forward / reverse)			
Drive method		4WD			
Brakes		Wet disc			
PTO		Live independent PTO (with hydraulic clutch)			
Rear		STD (540rpm)			
Mid		STD (2500rpm)			
Hydraulics					
Pump output	gpm (ℓ/min.)	6.2 (23.5)			
3-point hitch		SAE Category I			Optional
Lift capacity @ 24" behind pin	lbs. (kg)	680 (310)			
Steering		Hydrostatic Power Steering			
Tire size					
Front	Turf/Bar/Industrial	16x7.5-8 / 16x7.5-8 / N.A.		18x8.5-10 / 18x8.5-10 / 18x8.5-10	
Rear	Turf/Bar/Industrial	24x12-12 / 24x12-12 / N.A.		26x12-12 / 26x12-12 / 26x12-12	
Traveling speeds at rated engine rpm (Turf)					
Forward	mph (km/h)	0-7.8 (0-12.5)		0-8.4 (0-13.5)	
Reverse	mph (km/h)	0-5.9 (0-9.5)		0-6.5 (0-10.5)	
Dimensions					
Length with 3-point hitch	in. (mm)	95.5 (2425)			99.0(2515) w/ Front guard
Width	in. (mm)	44.1 (1120)		45.1 (1145)	
Height with ROPS	in. (mm)	81.9 (2080)		83.1 (2110)	
Wheelbase	in. (mm)	55.1 (1400)			
Ground clearance (front axle)	in. (mm)	7.6 (193)		8.4 (213)	
Tread	Front	in. (mm)			
	Rear	in. (mm)			
Turning radius (w/o brake)	feet (m)	7.5 (2.3)			
Tractor weight (w/ROPS)	lbs. (kg)	1336 (606)	1443 (650)	1521 (670)	1570 (712) *2

BX23S** Backhoe Specifications

Model	BT603	
Bucket cylinder digging force	lbf. (N)	1936 (8610)
Dipperstick cylinder digging force	lbf. (N)	1171 (5209)
Boom swing mechanism		One cylinder
Shipping weight (with 12" bucket)	lbs. (kg)	607 (275)
Transport height	in. (mm)	67.7 (1719)
Loading height	ft. (mm)	5' (1533)
Digging depth	ft. (mm)	6'1" (1842)
Swing pivot to rear axle center line	in. (mm)	28.6 (726)
Reach from swing pivot	ft. (mm)	8'7" (2612)
Bucket rotation	degrees	180
Swing arc	degrees	140
Angle of departure	degrees	20.1

*1SAE J1995 **2w/ Front guard, w/ control valve assy

*SAE J1995 **The loader and backhoe come standard on the BX23S model.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

BX23S** Loader Specifications

Model Type	LA340 Pin-on	LA340S Quick attach
Max. lift height (to bucket pivot pin)	in. (mm)	
	71.0 (1804)	
Dumping clearance	in. (mm)	52.1 (1323)
Dumping reach at max. lift height	in. (mm)	25.4 (646)
Maximum dump angle	degrees	
	45	
Reach with bucket on ground	in. (mm)	54.8 (1392)
Bucket rollback angle	degrees	
	29	
Digging depth	in. (mm)	4.9 (125)
Bucket width	in. (mm)	48 (1219)
Lift capacity (500mm fwd, max. height)	lbs. (kg)	509 (231)
Lift capacity (pivot pin, max. height)	lbs. (kg)	739 (335)
Breakout force (500mm fwd)	lbf. (N)	987 (4389)
Raising time / lowering time (w/o load)	second	
	3.3 / 2.5	
Bucket rollback time / dumping time	second	
	2.3 / 2.7	



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2017 Kubota Corporation

